GUIDELINES ON BEST AVAILABLE TECHNIQUES AND PROVISIONAL GUIDANCE ON BEST ENVIRONMENTAL PRACTICES

relevant to Article 5 and Annex C of the Stockholm Convention on Persistent Organic Pollutants

Motor vehicles, particularly those burning leaded gasoline



This publication may be reproduced in whole or in part in any form for educational or non-profit purposes without special permission, provided acknowledgement of the source is made. The Secretariat of the Stockholm Convention and UNEP would appreciate receiving a copy of any publication that uses this publication as a source. No use of this publication may be made for resale or for any other commercial purpose whatsoever without prior permission in writing from the United Nations Environment Programme.

Published by the Secretariat of the Stockholm Convention on Persistent Organic Pollutants in October 2008. For more information please contact:

Secretariat of the Stockholm Convention on Persistent Organic Pollutants United Nations Environment Programme International Environment House 11-13 chemin des Anémones CH-1219, Châtelaine, Geneva, Switzerland ssc@pops.int - www.pops.int

Designed and printed by: SRO-Kundig - Geneva

GUIDELINES ON BEST AVAILABLE TECHNIQUES AND PROVISIONAL GUIDANCE ON BEST ENVIRONMENTAL PRACTICES

relevant to Article 5 and Annex C of the Stockholm Convention on Persistent Organic Pollutants

CONTENTS

SECTION I: INTRODUCTION

I.A	Purpose
I.B	Structure of document and using guidelines and guidance
I.C	CHEMICALS LISTED IN ANNEX C: DEFINITIONS, RISKS, TOXICITY
I.D	ARTICLE 5 AND ANNEX C OF THE STOCKHOLM CONVENTION
I.E	Relationship to the Basel Convention
I.F	Relationship to other environmental concerns

SECTION II: CONSIDERATION OF ALTERNATIVES IN THE APPLICATION OF BEST AVAILABLE TECHNIQUES

- II.A CONSIDERATION OF ALTERNATIVES IN THE STOCKHOLM CONVENTION
- II.B THE STOCKHOLM CONVENTION AND NEW SOURCES
- II.C AN APPROACH TO CONSIDERATION OF ALTERNATIVES
- II.D OTHER CONSIDERATIONS OF THE STOCKHOLM CONVENTION

SECTION III: BEST AVAILABLE TECHNIQUES AND BEST ENVIRONMENTAL PRACTICES: GUIDANCE, PRINCIPLES AND CROSS-CUTTING CONSIDERATIONS

- III.A GUIDANCE
- III.B GENERAL PRINCIPLES AND APPROACHES
- III.C CROSS-CUTTING CONSIDERATIONS:
 - (I) CHEMICALS LISTED IN ANNEX C: FORMATION MECHANISMS
 - (II) WASTE MANAGEMENT CONSIDERATIONS
 - (III) CO-BENEFITS OF BEST AVAILABLE TECHNIQUES FOR CHEMICALS LISTED IN ANNEX C
 - (IV) MANAGEMENT OF FLUE GAS AND OTHER RESIDUES
 - (V) TRAINING OF DECISION MAKERS AND TECHNICAL PERSONNEL
 - (VI) TESTING, MONITORING AND REPORTING

SECTION IV: COMPILATION OF SUMMARIES FROM THE SOURCE CATEGORIES INCLUDED IN SECTIONS V AND VI

SUMMARIES OF SECTION V: SOURCE CATEGORIES INCLUDED IN PART II OF ANNEX C SUMMARIES OF SECTION VI: SOURCE CATEGORIES INCLUDED IN PART III OF ANNEX C

SECTION V: GUIDANCE/GUIDELINES BY SOURCE CATEGORIES: SOURCE CATEGORIES IN PART II OF ANNEX C

	WASTE INCINERATORS		
(I)	MUNICIPAL SOLID WASTE, HAZARDOUS WASTE AND SEWAGE SLUDGE		
(11)	MEDICAL WASTE		
	CEMENT KILNS FIRING HAZARDOUS WASTE		
PRODUCTION OF PULP USING ELEMENTAL CHLORINE OR CHEMICALS GENERATING ELEMENTAL CHLORINE			
	THERMAL PROCESSES IN THE METALLURGICAL INDUSTRY		
(I)	SECONDARY COPPER PRODUCTION		
(11)	SINTER PLANTS IN THE IRON AND STEEL INDUSTRY		
(111)	SECONDARY ALUMINIUM PRODUCTION		
(IV)	SECONDARY ZINC PRODUCTION		
N VI:	GUIDANCE/GUIDELINES BY SOURCE CATEGORIES: SOURCE		
	CATEGORIES IN PART III OF ANNEX C		
	OPEN BURNING OF WASTE, INCLUDING BURNING OF LANDFILL SITES		
	Thermal processes in the metallurgical industry not mentioned in Annex C Part II		
(I)	SECONDARY LEAD PRODUCTION		
(11)	PRIMARY ALUMINIUM PRODUCTION		
(111)	MAGNESIUM PRODUCTION		
()			
	CECOND LOV CTEEL DOODLICTION		
	(i) (i) (ii) (ii) (iv) (vv) DN VI: (i) (i) (ii) (ii) (ii)		

(V) PRIMARY BASE METALS SMELTING

VI.C	Residential combustion sources
VI.D	Fossil fuel-fired utility and industrial boilers
VI.E	Firing installations for wood and other biomass fuels
VI.F	Specific chemical production processes releasing chemicals listed in Annex C
VI.G	Сгематогіа
VI.H	MOTOR VEHICLES, PARTICULARLY THOSE BURNING LEADED GASOLINE
VI.I	Destruction of animal carcasses
VI.J	Textile and leather dyeing (with chloranil) and finishing (with alkaline extraction)
VI.K	Shredder plants for the treatment of end-of-life vehicles
VI.L	Smouldering of copper cables
VI.M	WASTE OIL REFINERIES

Guidance/guidelines by source category: Source categories in Part III of Annex C

Section

Part III Source category (h): Motor vehicles, particularly those burning leaded gasoline

CONTENTS

VI.H	Motor vehicles, particularly those burning leaded gasoline Introduction		
1.			
	1.1	Process description	9
	1.2	Fuels, engine types and emissions	9
2.	PCDD/PCDF formation and release		10
	2.1	Studies of PCDD/PCDF emissions	10
	2.2	Summary of findings	12
3.	Best available techniques and best environmental practices		13
4.	Regulations addressed to reduction of PCDD/PCDF emissions		13
Refere	ences		14
Table	s		
Table	1. PC	DD/PCDF emissions from motor vehicles	11



Summary

The major fuels used in motor vehicle transportation are gasoline and diesel. Liquefied petroleum gas, vegetable oil-based and other biofuels, and alcohol-oil mixtures are gaining importance.

PCDD and PCDF have been found in the emissions from motor vehicles fuelled with gasoline or diesel. The higher concentrations identified in emissions from vehicles run on leaded gasoline are due to the presence of chlorinated and brominated scavengers in the fuel.

As alternatives to leaded gasoline, the following fuels may be considered: unleaded gasoline (best when equipped with catalyst); diesel (best when equipped with diesel oxidation catalyst and particulate filter); liquefied petroleum gas; compressed natural gas; propane/butane gas; biofuels; and alcohol-oil mixtures.

Best available techniques include banning of halogenated scavengers, and fitting motor vehicles with an oxidation catalyst or particulate filter.

There are no measured data available for biofuels, alcohol-oil mixtures or liquefied petroleum gas, and no data for 2-stroke engines.

1. Introduction

1.1 Process description

For motor vehicles, the process description is relatively straightforward. The gasoline engine derives its power from the explosion of a mixture of air and gasoline, whereas in the diesel engine the fuel burns rather than explodes. The air-fuel mixture, when ignited, expands rapidly in a cylinder, forcing a piston from the top of the cylinder to the bottom. After its release from a vehicle, the exhaust gas is diluted approximately a thousandfold in the first few seconds and cooled down very rapidly (DEH 2004).

1.2 Fuels, engine types and emissions

The major fuels used in transportation are gasoline, diesel and liquefied petroleum gas. Most gasoline-powered internal combustion engines used today in cars, light trucks, motorcycles and other vehicles are 4-stroke engines. Like many combustion processes, internal combustion engines generate polychlorinated dibenzo-*p*-dioxins (PCDD) and polychlorinated dibenzofurans (PCDF) as unwanted byproducts (UNEP 2005).

Most small gasoline-powered internal combustion engines used today in boats, jet skis, mopeds, small motorcycles, tuk-tuks, lawnmowers, chainsaws and other vehicles and appliances are 2-stroke engines. These engines follow the same thermodynamic

combustion cycle as the 4-stroke engine; however, it consists of only two strokes, namely the combined exhaust and intake stroke, and the compression, ignition and combustion stroke. The most striking difference from the 4-stroke engine is the fact that all strokes occur during only one full revolution of the crankshaft. Lubrication is usually by oil added to the fuel. Therefore, higher amounts of pollutants may be released and efficiency may be lower compared to 4-stroke engines. However, the simplicity and low production cost of the 2-stroke engine make it an ideal motor for small-scale applications.

Diesel engines are used in heavy trucks, light trucks, passenger cars, heavy construction equipment, boats, generators, pumps and farm equipment, including tractors and other large equipment. They usually use diesel (light oil) and a 4-stroke cycle. Compression is used for ignition rather than a spark. Air is taken into the cylinder and compressed. Diesel fuel is added at high pressure and burnt. This results in a more efficient use of fuel and lower specific emissions. However, particle emissions in the form of soot are associated with the operation of diesel engines due to incomplete combustion, especially during start-up, warming and load changes. Particulate emissions from diesel engines are well known to contain high concentrations of polycyclic aromatic hydrocarbons.

Since PCDD/PCDF were detected for the first time in used motor oil (Ballschmiter et al. 1986), evidence has mounted that PCDD/PCDF are formed and emitted by the combustion processes in gasoline- and diesel-fuelled engines. Incomplete combustion and the presence of chlorine in the fuel, lubricant and air lead to the formation of PCDD/PCDF, chemicals listed in Annex C of the Stockholm Convention (Marklund et al. 1987, 1990; Schwind et al. 1991; Hutzinger et al. 1992; Gullett and Ryan 1997). Whereas for gasoline-powered engines the only relevant release vector for PCDD/PCDF is to air, diesel engines generate considerable amounts of deposits (soot). However, no measured data are available for PCDD/PCDF concentrations in diesel soot (UNEP 2005).

2. PCDD/PCDF formation and release

2.1 Studies of PCDD/PCDF emissions

Several European studies and one study in the United States of America evaluated PCDD/PCDF emissions from vehicles by measuring the presence of PCDD/PCDF in tunnel air. This approach has the advantage that it allows random sampling of large numbers of cars, including a range of ages and maintenance levels. The disadvantage of this approach is that it relies on indirect measurements, which may introduce unknown uncertainties and make interpretation of the findings difficult. Concerns have been raised that in tunnel studies resuspended particulates and absorbed PCDD/PCDF that have accumulated over time may lead to overestimates of emissions. This approach was therefore not deemed appropriate and the results of these studies were not considered in detail in the compilation of these guidelines. For further reading refer to the publications on tunnel and ambient air studies at the end of this section.

The first tailpipe emission study was performed by Marklund et al. (1987) on Swedish cars. Since then several studies either on running engines (passenger cars or trucks) or on motor stands or chassis dynamometers have been performed. Different fuels have been tested under varying conditions (simulating different traffic situations or varying loads). The results of the studies that report emissions based on fuel consumption are summarized in Table 1.

Fuel	Vehicle type	Emission (pg TEQ/L)	Reference
Leaded gasoline, 4-stroke	Passenger car, old: before muffler/in tailpipe	60/10	Marklund et al. 1990
	Passenger car, new: before muffler/in tailpipe	21/23	Marklund et al. 1990
	Passenger car	0.55–1.66	Schwind et al. 1991
Diesel	Truck	291	Geueke et al. 1999
	Heavy duty vehicles	29.3–47.7	Gullett and Ryan 1997
	Passenger car	2–141	Schwind et al. 1991
	Truck	4–88	Schwind et al. 1991
	No information	0.5, 0.6, 2.0	Kim et al. 2003
	Truck	1.20–103	Government of Japan 2003
	Passenger car	1.47–121	Government of Japan 2003
	Passenger car (chlorine: 12, 131, 259 ppm)	3–49	Dyke 2005
Unleaded gasoline, 4-stroke	Passenger car, old and new: before muffler or in tailpipe	3.5	Marklund et al. 1990
	Passenger car	5–22	Schwind et al. 1991
	Truck	0.42, 0.99	Government of Japan 2003
	Passenger car	0.34–16.42	Government of Japan 2003
Unleaded gasoline with catalyst, 4-stroke	Passenger car	2–3	Schwind et al. 1991

Table 1. PCDD/PCDF emissions from motor vehicles

In 1994, Hagenmaier and co-workers analysed the emissions of a diesel-fuelled bus (Hagenmaier 1994; Hagenmaier et al. 1995). PCDD/PCDF concentrations were around 1 pg/L for individual 2,3,7,8-substituted congeners, resulting in an I-TEQ of 0.01 ng I-TEQ/L. Thus, the 1994 results were much lower than the results obtained in 1990 (Hagenmaier et al. 1990). Whereas in 1990, mixed-halogenated dibenzo-*p*-dioxins

(PXDD) and dibenzofurans (PXDF) (X = Br, Cl) could be quantified, the 1994 emissions did not contain detectable PXDD/PXDF. Similarly, PCDD/PCDF concentrations were below the limit of quantification in an extract from a gasoline-powered motor vehicle (Hagenmaier et al. 1995). These results indicate that with the ban on the use of halogenated scavengers (in Germany: see BImSchV 1992), the main source of PCDD/PCDF (and PXDD/PXDF) was eliminated. The results also showed that cross-contamination did occur since the same containers were used for the transport of diesel, leaded and unleaded gasolines. In a test programme to determine the emission of PCDD/PCDF and polychlorinated biphenyls (PCB) from internal combustion diesel engines, in some runs PCB were detected at levels of 3.6 to 8.0 pg WHO-TEQ/L, which was low compared to the dioxin levels (Dyke 2005). There may have been some uncontrolled effect from insufficient engine conditioning that influenced the early test runs.

2.2 Summary of findings

The literature documenting results of European, Japanese (see also Miyabara et al. 1999), Korean, and United States studies gives evidence that:

- PCDD/PCDF emissions from vehicles burning unleaded fuels are lower than the emissions from vehicles burning leaded gasoline;
- The higher emissions from vehicles run on leaded fuels are due to the presence of brominated scavengers added to the fuels;
- Catalyst-equipped cars running on unleaded gasoline have lowest emissions;
- Limited testing shows that diesel oxidation catalysts are effective in reducing emissions of PCDD/PCDF;
- Diesel particulate filters are efficient in reducing PCDD/PCDF emissions from diesel-fuelled vehicles;
- Diesel-fuelled vehicles have lower emissions than leaded-gasoline-fuelled vehicles and slightly higher emissions than vehicles running on unleaded gasoline and equipped with catalytic converters;
- Use of motor oils with low chlorine content (in the diesel experiments) did not result in lower PCDD/PCDF emissions.

The situation is not clear as to the influence of the age of the vehicles. Whereas Marklund et al. (1990) found higher emissions in older vehicles, the German study (Schwind et al. 1991; Hutzinger et al. 1992) did not find such dependence.

There are no measured data available for the following vehicle engine types:

- 2-stroke engines;
- Utilizing liquefied petroleum gas;
- Utilizing alcohol-oil mixtures;
- Utilizing biofuels (canola, etc.)

3. Best available techniques and best environmental practices

Best available techniques to reduce PCDD/PCDF emissions from motor vehicles may include the following:

- Prohibition of halogenated scavengers;
- Prohibition of the use of leaded gasoline;
- Installation of diesel oxidation catalysts, particulate filters and catalytic converters;
- Alternatives to gasoline engine (electricity, solar light and fuel cell).

Best environmental practices may include:

- Avoidance policies such as greater fuel efficiency should be encouraged. Alternative modes of transport, including cycling, rail and other public transportation, should be promoted;
- Separation of transport containers according to the fuel (for example, do not transport leaded gasoline containing halogenated scavengers in containers that are also being used for the transport of diesel or unleaded gasoline);
- Prohibition of the use of leaded gasoline;
- Promotion of vehicles with low fuel consumption;
- Education to identify driving conditions that have low pollutant formation and release;
- Good maintenance of the vehicle.

4. Regulations addressed to reduction of PCDD/PCDF emissions

In Japan, the Special Measures Law on Dioxins (enforced in 1999) regulates concentrations of PCDD/PCDF emissions from specific sources, in which emission gases from motor vehicles are not included. With regard to motor vehicle fuel, 100% lead-free gasoline was achieved in the 1980s and sales of leaded gasoline were prohibited by the law on lead, benzene and sulphur. In Tokyo metropolitan area, diesel vehicles have to be equipped with diesel particulate filters.

In Germany, the 19th BImSchV prohibits the use of halogenated scavengers in motor vehicles as a measure to reduce PCDD/PCDF emissions from motor vehicles fuelled with leaded gasoline (BImSchV 1992).

References

Ballschmiter K., Buchert H., Niemczyk R., Munder A. and Swerev M. 1986. "Automobile Exhausts versus Municipal Waste Incineration as Sources of the Polychlorodibenzodioxins (PCDD) and - furans (PCDF) found in the Environment." *Chemosphere* 15:901–915.

BImSchV. 1992. 19. Verordnung zur Durchführung des Bundesimmissionsschutzgesetzes vom 24.07.1992 (Verordnung über Chlor- und Bromverbindungen als Kraftstoffzusatz - 19. BImSchV). Bundesgesetzblatt Teil 1, Jahrgang 1992, 75 (Ordinance on ban of halogenated scavengers, Germany).

DEH (Department of the Environment and Heritage, Australia). 2004. *Dioxins Emissions from Motor Vehicles in Australia*. Technical Report No. 2, National Dioxins Programme. Australian Government, Department of the Environment and Heritage.

Dyke P.H., Sutton M. 2005. "The Effect of Lubricating Oil on Diesel Engine PCDD/F and PCB Emissions." Organohalogen Compd. 67:2189–2191.

Dyke P.H., Sutton M., Wood D. 2006. Study on the effect of chlorine in lubricating oil on emissions of PCDD/F from a diesel engine. *Organohalogen Compd 68*.

Geueke K.-J., Gessner A., Quass U., Bröker G. and Hiester E. 1999. "PCDD/F Emissions from Heavy Duty Vehicle Diesel Engines." *Chemosphere* 38:2791–2806.

Government of Japan. 2003. *Inventory of PCDDs/DFs Emissions*. Government of Japan, Ministry of the Environment. www.env.go.jp/air/report/h15-05/index.html.

Gullett B. and Ryan J.V. 1997. "On-Road Sampling of Diesel Engine Emissions of Polychlorinated Dibenzo-*p*-dioxin and Polychlorinated Dibenzofuran." *Organohalogen Compd.* 32:451–456.

Hagenmaier H. 1994. "Contributions of Diesel-Powered Vehicles and Wood Burning to Overall PCDD/PCDF Emissions." *Organohalogen Compd.* 20:267–270.

Hagenmaier H., Dawidowsky N., Weberuss U., Hutzinger O., Schwind K.-H., Thoma H., Essers U., Buhler B. and Greiner R. 1990. "Emission of Polyhalogenated Dibenzodioxins and Dibenzofurans from Combustion Engines." *Organohalogen Compd.* 2:329–334.

Hagenmaier H., Krauss P., Vatter J. and Walczok M. 1995. "Eintrag und Verbleib von PCDD/PCDF: Bedeutung der Einträge durch Automobilabgase und Holzfeuerungen." *Organohalogen Compd.* 22:49–54.

Hutzinger, O., Hagenmaier H., Essers U., Bessy E., Schwind K.-H., Thoma H., Dawidowsky N., Weberuss U., Betz U., Bühler U. and Greiner R. 1992. "Untersuchungen zur Emission halogenierter Dibenzodioxine und Dibenzofurane aus Verbrennungsmotoren beim Betrieb mit handelsüblichen Betriebsstoffen." GSF-Forschungszentrum, Munich, Germany.

Kim K.-S., Hong K.-H., Ko Y.-H., Yoon K.-D. and Kim M.-G. 2003. "Emission Characteristics of PCDD/Fs in Diesel Engine with Variable Load Rate." *Chemosphere* 53:601–607.

Larssen S., Brevik E.M. and Oehme M. 1990. Emission Factors of PCDD and PCDF for Road Vehicles Obtained by Tunnel Experiment." *Organohalogen Compd.* 1:453-456.

Marklund S., Andersson R., Tysklind M., Rappe C., Egebäck K.E., Bjorkman E. and Grigoriadis V. 1990. "Emissions of PCDDs and PCDFs in Gasoline and Diesel Fueled Cars." *Chemosphere* 20:553–561.

Marklund S., Rappe C., Tysklind M. and Egebäck K. 1987. "Identification of Polychlorinated Dibenzofurans and Dioxins in Exhausts from Cars Run on Leaded Gasoline." *Chemosphere* 16:29–36.

Miyabara Y., Hashimoto S., Sagai M. and Morita M. 1999. "PCDDs and PCDFs in Vehicle Exhaust Particles in Japan." *Chemosphere* 39:143–150.

Oehme M., Larssen S. and Brevik E.M. 1991. "Emission Factors of PCDD/CDF for Road Vehicles Obtained by a Tunnel Experiment." *Chemosphere* 23:1699–1708.

Rappe C., Kjeller L.O., Bruckmann P. and Hackhe K.H. 1988. "Identification and Quantification of PCDD/CDFs in Urban Air." *Chemosphere* 17:3–20.

Wevers M., De Fre R. and Rymen T. 1992. "Dioxins and Dibenzofurans in Tunnel Air." Organohalogen Compd. 9:321–324.

Schwind K.-H., Thoma H., Hutzinger O., Dawidowsky N., Weberuss U., Hagenmaier H., Bühler U., Greiner R., Essers U. and Bessey E. 1991. "Emission halogenierter Dibenzodioxine (PXDD) und Dibenzofurane (PXDF) aus Verbrennungsmotoren beim Betrieb mit handelsüblichen Betriebsstoffen." *UWSF-Z Umweltchem. Oekotox* 3:291–298.

UNEP (United Nations Environment Programme). 2005. *Standardized Toolkit for Identification and Quantification of Dioxin and Furan Releases*. Edition 2.1.UNEP, Geneva.

http://www.pops.int UNEP/SSC/BATBEP/2008/13